



# 20/250 Precision Matched Passive LMA Double Clad PM Fiber

Coherent | Nufern's Polarization Maintaining LMA (PLMA) passive double clad fiber is ideal for high power fiber lasers and amplifiers used in military, industrial, and medical applications. This fiber features a 20 micron diameter core and 250 micron diameter clad size with a low NA (0.09) core. It is precision matched to its active ErYb-doped 20P/250 PLMA matched counterpart to ensure excellent splice compatibility and low loss. As with all Coherent | Nufern standard Large Mode Area (LMA) fibers, this fiber is proof-tested to 100 kpsi, an industry requirement for long term reliability. The fiber utilizes the latest fiber design and NuCOAT-FA coating technology to ensure excellent preservation of beam quality and extended operating life at the high power levels demanded by today's industrial fiber laser applications.

## Typical Applications

- High peak power amplifiers
- LIDAR
- Material processing
- Non-linear optics/frequency doubling

## Features & Benefits

- NuCOAT-FA fluoroacrylate coating — Greater fiber durability in extreme environmental operating & storage conditions
- LMA core design — Useful for transmitting high CW powers
- "Few" moded core design — Easy to maintain single mode LP01 beam through fiber & components
- PANDA-style stress structure for increased birefringence — Superior optical performance and uniformity
- All fiber proof tested to > 100 kpsi — Critical for ensuring long term reliability when coiling

## Optical Specifications

Operating Wavelength	800 – 1650 nm
Core NA	0.090 ± 0.007
First Cladding NA (5%)	≥ 0.46
Cladding Attenuation	≤ 15.0 dB/km @ 1095 nm
Birefringence	nominal $1.5 \times 10^{-4}$

## PLMA-GDF-20/250-09M

## Geometrical & Mechanical Specifications

Cladding Diameter	250.0 ± 5.0 μm
Core Diameter	20.0 ± 1.5 μm
Coating Diameter	350.0 ± 10.0 μm
Core/Clad Offset	≤ 2.00 μm
Clad Non-Circularity	≤ 2.0 %
Coating Material	Low Index Acrylate
Proof test Level	≥ 100 kpsi (0.7 GN/m <sup>2</sup> )

Active fiber PLMA-EYDF-20P/250-XPB



7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • E-mail [info@nufern.com](mailto:info@nufern.com) • [www.nufern.com](http://www.nufern.com) • Nufern products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.

NU0322- 01/22/2018