



# FUD-3440, Revision: B MM-GDF-25/250-11FA Optical Fiber

You have selected an application designed fiber, not fully released which may have a longer lead time than our standard products.

Parameter	Min	Nom	Max	Unit	Compliance
Operating Wavelength	1060		2100	nm	Design
Cladding Attenuation at 1095nm	0		15	dB/km	Measured
Core NA	0.1		0.12		Design
Cladding NA (5%)	0.46				Design
Core Diameter	23		27	µm	Measured
Clad Diameter	245		255	µm	Measured
Coating Diameter	380		420	µm	Measured
Proof test Level	100		150	kpsi	Measured
Comments	Photosensitivity Requirements: Intrinsically photosensitive fiber Coating Requirements: Low Index Polymer Other Requirements: Round fiber				



7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • E-mail [info@nufern.com](mailto:info@nufern.com) • [www.nufern.com](http://www.nufern.com) •  
 Nufern products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.