



Device Characteristics

Configuration	Port Identification	Fiber Type	Notes
Pump input port	Ports 1-7, excluding 4	220/242 um NA=0.22	
Signal input port	Port 4	10/125 um NA=0.08/0.46	
Output port	Port 8	20/400 um NA=0.06/0.46	

Optical Performance Specifications

Parameters	Min.	Typ.	Max.	Units	PDR	Notes
Operating wavelength - Signal	1040		1080	nm		
Operating wavelength - Pump	800		1000	nm		
Maximum insertion loss - Signal			0.5	dB	Yes	1,2
Maximum insertion loss - Pump			0.1	dB	Yes	1,3
Optical return loss - Pump	45			dB		1,3

Mechanical and Environmental Specifications

Parameters	Value	Notes
Power handling	200 W/port	4
Dimensions	60.0mm x 12.0mm x 6.5mm	
Pigtail length	> 1000mm on all ports	5

Note(s)

- [1] Parameters are specified at room temperature
- [2] Underfilled condition
- [3] Fully filled condition
- [4] Heatsinking is required, see application note on website
- [5] For safe handling of DCF fiber, see application note on website

Made in Canada

400 Montpellier Blvd, Montreal, QC, Canada, H4N 2G7, +1(514)748-4848
 www.itftechnologies.com

2013MA06

ISO 9001:2008

This Product is
 ROHS
 Compliant
 EU Directive 2011/65/EC