



Device Characteristics

Configuration	Port Identification	Fiber Type	Notes
Pump input port	Ports 1-3	105/125 um NA=0.22	
Output port	Port 4	200/220 um NA=0.22	

Optical Performance Specifications

Parameters	Min.	Typ.	Max.	Units	PDR	Notes
Operating wavelength	800		1000	nm		
Maximum insertion loss - Pump			0.5	dB	Yes	1,2
Optical return loss - Pump	45			dB		1,2

Mechanical and Environmental Specifications

Parameters	Value	Notes
Power handling	100 W/port	3
Maximum reverse pump light	10 W	
Dimensions	60.0mm x 12.0mm x 6.5mm	
Product code + A: Pigtail length	> 1000mm on all ports	
Product code + B: Pigtail length	> 2000mm on all ports	
Product code + C: Pigtail length	> 3000mm on all ports	

Note(s)

- [1] Parameters are specified at room temperature
- [2] Designed to be used at NA=0.15
- [3] Heatsinking is required, see application note on website

Made in Canada

400 Montpellier Blvd, Montreal, QC, Canada, H4N 2G7, +1(514)748-4848

www.itftechnologies.com

2016JN15

ISO 9001:2008

This Product is
 ROHS
 Compliant
 EU Directive 2011/65/EC